Previous Doc

Next Doc

Go to Doc#

First Hit

Generate Collection

L5: Entry 4 of 17

File: JPAB

Sep 3, 2002

PUB-NO: JP02002248850A

DOCUMENT-IDENTIFIER: JP 2002248850 A

TITLE: CAST GLOSSY PAPER FOR INK JET RECODING AND MANUFACTURING METHOD THEREFOR

PUBN-DATE: September 3, 2002

INVENTOR-INFORMATION:

NAME

COUNTRY

TAMAKI, MASAYOSHI TSUCHIYA, NAOKI WATANABE, KAZUKI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

HOKUETSU PAPER MILLS LTD

APPL-NO: JP2001048883

APPL-DATE: February 23, 2001

INT-CL (IPC): <u>B41 M 5/00</u>; <u>D21 H 19/36</u>; <u>D21 H 27/00</u>

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a cast glossy paper for <u>ink jet</u> recording, on which a high quality recording image, especially of a high recording image density can be provided especially with an <u>ink jet</u> dye ink on a cast-coated paper having a high evenness and lustrous properties, and its manufacturing method.

SOLUTION: This cast glossy paper for ink jet recording is a cast-coated paper, in which an ink accepting layer made of a pigment and a transparent binder is provided on at least one side of a base paper and a cast glossy layer including a pigment for giving gloss and a binder is formed on the ink accepting layer. The cast glossy layer is a coating surface solidifyingly treated with a coagulating agent. The cast-coated paper is produced by compression-bonding the cast glossy surface under its wet state with a heated and mirror-finished metal surface. The coating weight of the ink accepting layer lies within the range of 5 to 15 g/m2 and its haze is 70% or less. At the same time, the pigment in the ink accepting layer is a porous synthetic silica having a particle diameter of 2 to 15 μ m.

COPYRIGHT: (C) 2002, JPO

Previous Doc Next Doc Go to Doc#